



EMT Conduit Fittings

EMT 90 Degree Elbow, PG



Material	Steel Q195
Finish	Pre-galvanized
Standard	ANSI C80.3
Thread	No threaded
Size	1/2" to 4"
Usage	Used to connect EMT Conduit together to allow for 90 degree bends.

Cat.No. 90°	Cat.No. 45°	Size
8300	8310	1/2"
8301	8311	3/4"
8302	8312	1"
8303	8313	1 1/4"
8304	8314	1 1/2"
8305	8315	2"
8306	8316	2 1/2"
8307	8317	3"
8308	8318	3 1/2"
8309	8319	4"





EMT 90 Degree Elbow, ZCDG



Material	Steel Q195
Finish	Hot dip galvanized
Standard	UL 797
Thread	No threaded
Size	1/2" to 4"
Usage	Used to connect EMT Conduit together to allow for 90 degree bends.

Cat.No. 90°	Cat.No. 45°	Size
8300	8310	1/2"
8301	8311	3/4"
8302	8312	1"
8303	8313	1 1/4"
8304	8314	1 1/2"
8305	8315	2"
8306	8316	2 1/2"
8307	8317	3"
8308	8318	3 1/2"
8309	8319	4"



EMT 45 Degree Elbow,PG



Material	Steel Q195
Finish	Pre-galvanized
Standard	ANSI C80.3
Thread	No Thread
Size	1/2" to 4"
Usage	Used to connect EMT Conduit together to allow for 90 degree bends.

Cat.No. 90°	Cat.No. 45°	Size
8300	8310	1/2"
8301	8311	3/4"
8302	8312	1"
8303	8313	1 1/4"
8304	8314	1 1/2"
8305	8315	2"
8306	8316	2 1/2"
8307	8317	3"
8308	8318	3 1/2"
8309	8319	4"

EMT 45 Degree Elbow, PG



Material	Steel Q195
Finish	Pre-galvanized
Standard	ANSI C80.3
Thread	No threaded
Size	1/2", 3/4", 1"
Usage	Used to connect EMT Conduit together to allow for 90 degree bends.



EMT Set Screw Coupling



Material	Zinc/ Steel
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Used to join two length of Electrical Metallic Tubing.

Cat.No.	Cat.No.	Conduit Size
SSCN-050	Z-50S	1/2"
SSCN-075	Z-75S	3/4 "
SSCN-100	Z-100S	1"
SSCN-125	Z-125S	1 1/4"
SSCN-150	Z-150S	1 1/2"
SSCN-200	Z-200S	2"
SSCN-250	Z-250S	2 1/2'
SSCN-300	Z-300S	3"
SSCN-400	Z-400S	4"



EMT Set Screw Connector



Material	Zinc/ Steel
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Used to join Electrical Metallic Tubing to knock-outs in concrete-tight box or dry location.

Cat.No.	Cat.No.	Cat.No.	Conduit Size
	Non-Insulated	Insulated	
SSCN-050	ZC-50S	ZC-50SI	1/2"
SSCN-075	ZC-75S	ZC-75SI	3/4"
SSCN-100	ZC-100S	ZC-100SI	1"
SSCN-125	ZC-125S	ZC-125SI	1 1/4"
SSCN-150	ZC-150S	ZC-150SI	1 1/2"
SSCN-200	ZC-200S	ZC-200SI	2"
SSCN-250	ZC-250S	ZC-250SI	2 1/2"
SSCN-300	ZC-300S	ZC-300SI	3"
SSCN-350	ZC-350S	ZC-350SI	3 1/2"
SSCN-400	ZC-400S	ZC-400SI	4"

EMT Compression Connector



Material	Zinc/ Steel
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Used to join Electrical Metallic Tubing to knock-outs in concrete-tight box or dry location applications.

Zinc		Steel		
Cat.No.	Cat.No.	Cat.No.	Cat.No.	Conduit Size
Non-Insulated	Insulated	Non-Insulated	Insulated	/
CCN-050	CCN-050	ZC-50S	ZC-50SI	1/2"
CCN-075	CCN-075	ZC-75S	ZC-75SI	3/4"
CCN-100	CCN-100	ZC-100S	ZC-100SI	1"
CCN-125	CCN-125	ZC-125S	ZC-125SI	1 1/4"
CCN-150	CCN-150	ZC-150S	ZC-150SI	1 1/2"
CCN-200	CCN-200	ZC-200S	ZC-200SI	2"
/	/	ZC-250S	ZC-250SI	2 1/2"
/	/	ZC-300S	ZC-300SI	3"
/	/	ZC-350S	ZC-350SI	3 1/2"
/	/	ZC-400S	ZC-400SI	4"

EMT Compression Coupling



Material	Zinc/ Steel
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Used to join two length of Electrical Metallic Tubing.

Zinc Cat.No.	Steel Cat.No.	Conduit Size
CCP-050	ZCC-50S	1/2"
CCP-075	ZCC-75S	3/4"
CCP-100	ZCC-100S	1"
CCP-125	ZCC-125S	1 1/4"
CCP-150	ZCC-150S	1 1/2"
CCP-200	ZCC-200S	2"
/	ZCC-250S	2 1/2"
/	ZCC-300S	3"
/	ZCC-350S	3 1/2"
/	ZCC-400S	4"



STEEL PIPE SINCE 1991
BAOLAI

EMT Conduit Bushing



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Thread	NPT/ NPSL
Size	1/2" to 4"
Usage	Use with lockout to terminate threaded Rigid or IMC Conduit to an outlet box.

Zinc Cat.No.	Steel Cat.No.	Conduit Size
CB-050	CB-050I	1/2"
CB-075	CB-075I	3/4"
CB-100	CB-100I	1"
CB-125	CB-125I	1 1/4"
CB-150	CB-150I	1 1/2"
CB-200	CB-200I	2"
CB-250	CB-250I	2 1/2"
CB-300	CB-300I	3"
CB-350	CB-350I	3 1/2"
CB-400	CB-400I	4"



Lloyd's Register



Phone: +86 022 83377302

Email: info@baolaisteel.com

Grounding Bushing Insulated



Material	Zinc/ Iron
Finish	Galvanized
Standard	UL 514B
Thread	NPSL
Size	1/2" to 6"
Usage	Use with lockout to terminate threaded Rigid or IMC Conduit to an outlet box.

Zinc	Iron Cat.No.	Conduit Size
Zinc with Grounding	CB-050MG	1/2"
	CB-075MG	3/4"
	CB-100MG	1"
	CB-125MG	1 1/4"
	CB-150MG	1 1/2"
	CB-200MG	2"
	CB-250MG	2 1/2"
	CB-300MG	3"
	CB-350MG	3 1/2"
	CB-400MG	4"
/	CB-450MG	5"
/	CB-500MG	6"

EMT Capped Corner Coupling



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	1/2" 3/4" 1"
Usage	Use to facilitate pulling conductors through a 90 degree bend in a run of steel Electrical Metallic Tubing where it is essential to make tight turns within limited available space.

EMT Connector Set Screw 90 Degree



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	3/4", 1", 1-1/4"
Usage	Use to facilitate pulling conductors through a 90 degree bend in a run of steel Electrical Metallic Tubing where it is essential to make tight turns within limited available space.

EMT Compression Connector 90 Degree



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	3/4", 1", 1-1/4"
Usage	Use to facilitate pulling conductors through a 90 degree bend in a run of steel Electrical Metallic Tubing where it is essential to make tight turns within limited available space.

EMT to Flex Coupling



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	1/2", 3/4", 1"
Usage	Used to provide a transition from Electrical Metallic Tubing to flexible metal conduit. Electrical Metallic Tubing side is set-screw and flex side is squeeze type.

EMT to EMT Pull Corner Elbow



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	1/2" , 3/4" , 1"
Usage	Use to facilitate pulling wires through a 90 degree bend in a run of EMT Pipe, Removable cover gives ample access to wiring.

EMT Offset Connector



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	1/2" , 3/4" , 1"
Usage	Use to make a slight adjustment in terminating the end of a run of steel EMT Pipe to an enclosure or box where an offset is required.

EMT Set Screw Service Entrance Cap



Material	Zinc
Finish	Galvanized
Standard	UL 514B
Size	1/2" to 4"
Usage	Use in an overhead service entrance. Mounts on top of EMT Pipe Clamp on type.

EMT One Hole Strap,EG



Material	Steel
Finish	Electro-galvanized
Standard	UL E365032
Size	1/2" to 2"
Usage	Snap-on type EMT strap with one hole. Inverted rib for strength.



EMT Two Hole Strap,EG



Material	Steel
Finish	Electro-galvanized
Standard	UL 2239
Size	1/2" to 2"
Usage	Use to support EMT Conduit to a mounting surface.

EMT One Hole Strap, Pre-Galvanized



Material	Steel
Finish	Pre-galvanized
Size	1/2" to 2"
Usage	Snap-on type EMT strap with one hole Inverted rib for strength.

EMT Two Hole Strap,PG



Material	Steel
Finish	Pre-galvanized
Size	1/2" to 2"
Usage	Use to support EMT Conduit to a mounting surface.



Lloyd's Register





EMT Conduit Spacer Bar Saddle



Material	Steel
Finish	Electro-galvanized
Size	3/4" to 1"
Usage	Use to support EMT Conduit to a mounting surface.

EMT Conduit Hanger



Material	Steel
Finish	Electro-galvanized
Standard	UL 2239
Size	1/2" to 4"
Usage	Use to secure and suspend EMT/IMC/Rigid Conduit from overhead supports.



EMT Strut Clamp



Material	Steel
Finish	Electro-galvanized
Standard	UL 2239
Packing	Assembled with nut and bolt
Size	1/2" to 2"
Usage	Use to support EMT Pipe to Steel Channel.

EMT Conduit Fastener



Material	Steel
Finish	Black Enamel
Size	1/2"-3/4" to 2"
Usage	Use to secure and suspend EMT/IMC/Rigid Conduit from overhead supports.



Locknut



Material	Steel/ Zinc/ Stainless Steel
Finish	Electro-galvanized
Standard	UL 514B
Thread	NPSM
Size	1/2" to 4"
Stainless Steel Size	1/2" to 6"
Usage	Use on end of threaded Connectors to a steel outlet box or metal enclosure.

Knockout Seal



Material	Steel
Finish	Pre-galvanized
Size	1/2" to 2"
Usage	Designed to cover exposed knock-out holes in steel boxes and other metal enclosures.





STEEL PIPE SINCE 1991
BAOLAI

EMT Aluminum Conduit Bender



Material	Aluminum
Thread	NPSM
Size	1/2", 3/4", 1"

EMT Conduit Bender with Handle



Material	Aluminum
Thread	NPSM
Size	1/2", 3/4", 1"



Phone: +86 022 83377302

Email: info@baolaisteel.com

IMC Conduit Fittings

IMC Conduit 90° Elbow,HDG



Material	Steel
Finish	Hot dip galvanized
Standard	UL 1242 / ANSI C80.6
Thread	NPT
Size	1/2" to 4"
Usage	Used to connect IMC Conduit together to allow for 90 degree bends.

IMC Conduit 90° Elbow,PG



Material	Steel
Finish	Pre-galvanized
Standard	ANSI C80.6
Thread	NPT
Size	1/2" to 2"
Usage	Used to connect IMC Conduit together to allow for 90 degree bends.

Rigid Conduit 90°
 Elbow, HDG



Material	Steel
Finish	Hot Dip Galvanized
Standard	UL 6
Thread	NPT
Size	1/2" to 6"
Usage	installed on conduit raceways for the interconnection of conduit runs and other fittings.

Rigid Conduit 45°
 Elbow, HDG



Material	Steel
Finish	Hot Dip Galvanized
Standard	UL
Thread	NPT
Size	1/2" to 6"
Usage	installed on conduit raceways for the interconnection of conduit runs and other fittings.

IMC Coupling, EG



Material	Steel
Finish	Galvanized
Standard	UL 1242
Thread	NPSL
Size	1/2" to 4"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Coupling, EG



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 6"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Coupling, HDG



Material	Steel
Finish	Hot dip galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 6"
Usage	Used to join two lengths of threaded Rigid or IMC conduit.

Rigid Set Screw Connector



Material	Steel
Finish	Zinc Plated
Standard	UL 514B
Size	1/2" to 2"
Usage	Used to bond unthreaded Rigid or IMC conduits to electrical junction boxes or electrical enclosures.

Rigid Set Screw Coupling



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to bond two length of unthreaded Rigid or IMC conduits.

Rigid Compression Connector



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to join IMC / Rigid Conduit to knock-outs in concrete-tight box or damp location applications.

Rigid Compression Coupling



Material	Steel
Finish	Galvanized
Standard	UL 6 / ANSI C80.1
Thread	NPT
Size	1/2" to 2"
Usage	Used to join two length of IMC / Rigid Conduit.

Rigid Watertight Hub



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 4"
Usage	Connect rigid or IMC conduit to a load center or other metal enclosure where a weather-tight joint is required.

Grounding Watertight Hub



Material	Malleable Iron
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 6"
Usage	Connect rigid or IMC conduit to a load center or other metal enclosure where a weather-tight joint is required.

Reducing Bushing



Material	Steel
Finish	Galvanized
Thread	NPT
Size	1/2" to 4"
Usage	Use to reduce the entry size of a run of threaded IMC / Rigid conduit.

Stainless Steel Reducing Bushing



Material	Stainless Steel
Finish	SS304 / SS316
Thread	NPSL
Size	1/2" to 4"
Usage	Use to reduce the entry size of a run of threaded IMC / Rigid conduit.

Rigid Male Enlarger



Material	Malleable Iron
Finish	Galvanized
Thread	NPT
Size	1/2" to 1"
Usage	Adapt an outlet hole to next large size.

Rigid Male Enlarger, EG



Material	Steel
Finish	Galvanized
Thread	NPT
Size	1/2" to 1"
Usage	to use with IMC/Rigid Pipe

Pull Corner Elbow Rigid to Rigid



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 1"
Usage	Use to facilitate pulling wires through a 90 degree bend in a run of Rigid or IMC conduit.

Pull Corner Elbow Rigid to Box



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 1"
Usage	Use as a wire pulling elbow to facilitate wire pulling through a sharp bend in a run of Rigid Conduit.

Offset Nipple



Material	Zinc Die Cast
Finish	Galvanized
Standard	UL 514B
Thread	NPT
Size	1/2" to 2"
Usage	Use to provide an offset connection between two outlet boxes or metal enclosures.

Electroform Concrete Slab Pipe Inserts-90 Degree



Material	Malleable Iron
Finish	Zinc Plated
Standard	UL 514B
Thread	NPSM
Size	1/2" to 1"
Usage	For conduit installed in poured concrete slabs. Nail, screw or tack-weld insert to concrete deck form.

Electroform Concrete Slab Pipe Inserts-Straight

EF-50 EF-75 EF-100



Material	Malleable Iron
Finish	Zinc Plated
Standard	UL 514B
Thread	NPSM
Size	1/2" to 1"
Usage	For conduit installed in poured concrete slabs. Nail, screw or tack-weld insert to concrete deck form.

Rigid Conduit Nipple



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 4"
Usage	Use to extend the length of a run of Rigid or IMC conduit or to connect two steel outlet boxes or metal enclosures together.

Chase Nipple



Material	Zinc
Finish	Galvanized
Thread	NPT
Size	3/4", 1"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

Chase Nipple, Insulated



Material	Zinc
Finish	Galvanized
Thread	NPT
Size	3/4", 1"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

Steel Chase Nipple



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 6"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

Steel Chase Nipple, Insulated



Material	Steel
Finish	Galvanized
Standard	UL6
Thread	NPT
Size	1/2" to 6"
Usage	Used with threaded female conduit couplings to connect conduits to electrical boxes and enclosures or are used with locknuts to connect two junction boxes.

3-Piece Union



Material	Malleable Iron
Finish	Galvanized
Standard	UL
Thread	NPSL
Size	1/2" to 6"
Usage	Used to connect threaded Rigid or IMC Conduit that are not able to be turned.

3-Piece Union, Steel



Material	Steel
Finish	Galvanized
Standard	UL
Thread	NPSL
Size	1/2" to 6"
Usage	Used to connect threaded Rigid or IMC Conduit that are not able to be turned.

Rigid Union Male



Material	Steel
Finish	Galvanized
Standard	UL
Thread	NPT
Size	1/2" to 4"
Usage	used to connect conduit to a conduit fitting or junction box or a device enclosure.

Rigid Union Female



Material	Steel
Finish	Galvanized
Standard	UL 1242
Thread	NPSL
Size	1/2" to 4"
Usage	used to connect conduit to a conduit fitting or a device enclosure.

Service Entrance Cap Threaded type



Material	Aluminum
Standard	UL 514B
Thread	NPSL
Size	1/2" to 4"

IMC/Rigid One Hole Strap, EG



Material	Galvanized Steel
Size	1/2" to 6"
Usage	Snap-on type Rigid strap with one hole Inverted rib for strength.

IMC/Rigid Two Hole Strap, EG



Material	Galvanized Steel
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 3-1/2", 4"
Usage	Snap-on type Rigid strap with one hole Inverted rib for strength.

Rigid Strut Clamp



Material	Galvanized Steel
Finish	Zinc Plated
Standard	UL E365032
Size	1/2" to 8"
Usage	Use to support IMC/Rigid Conduit from strut channel.

Rigid Conduit Hanger



Material	Steel
Finish	Electro-galvanized
Standard	UL 2239
Packing	Assembled with nut and bolt
Size	1/2" to 4"
Usage	Use to secure and suspend EMT/IMC/Rigid Conduit from overhead supports.